


TEL: (760) 398-3002 WWW.COACHELLA.ORG



DECK JOIST SPANS (douglas fir #2 or better)		
SIZE	SPACING	SPA
2 x 6	12" o.c. 16" o.c. 24" o.c.	10' - 6 9' - 0" 7' - 6"
2 x 8	12" o.c. 16" o.c. 24" o.c.	14' – 0 12' – 0 9' – 6"
2 × 10	10" 0 0	15' 0"

(douglas fir #2 or better)		
SIZE	SPACING	SPAN
2 x 6	12" o.c.	10' - 6"
	16" o.c. 24" o.c.	9' - 0" 7' - 6"
2 x 8	12" o.c. 16" o.c.	14' – 0" 12' – 0"
	24" o.c.	9' – 6"
2 x 10	16" o.c. 24" o.c.	15' – 0" 12' – 0"
2 x 12	24" o.c.	14' - 0"
4 x 6	12" o.c. 16" o.c. 24" o.c.	14' – 6" 13' – 6" 11' – 6"
4 x 8	24" o.c.	15' – 0"
4 x 10	32" o.c.	15' - 0"

TABLE "A"

TABLE "B" **HEADER SIZING & SPANS**

(douglas fir #2 or better)

JOIST SPAN	HEADER	
SPAN	SIZE	SPAN
UPTO 8'-0"	4 X 8	8'-0"
	4 X 10	10'-0"
	4 X 12	11'-6"
	6 X 12	14'-0"
8'-1" - 10'-0"	4 X 8	7'-6"
	4 X 10	9'-6"
	4 X 12	11'-0"
	6 X 12	13'-0"
10'-1" - 12'-0"	4 X 8	7'-0"
	4 X 10	9'-0"
	4 X 12	10'-0"
	6 X 12	12'-0"
12'-1" - 15'-0"	4 X 8	6'-6"
	4 X 10	8'-0"
	4 X 12	9'-6"
	6 X 12	11'-0"

TABLE "C" LEDGER BOLT SPACING

(3/8 dia. X 6" lag bolts - see note 1)

4	DECK JOIST SPAN	SPACING
╛	8'-0" OR LESS	8" O.C.
_	8'-1" TO 10'-0"	6" O.C.
_	10'-1" TO 12'-0"	5-1/2" O.C.
4	12'-1" TO 14'-0"	4-1/2" O.C.
4	14'-1" TO 15'-0"	4" O.C.

NOTES:

- Ledger Bolts shall be 3/8" dia. x 6" long with 1/ 4" dia. pre drilled holes. Bolts are to be placed staggered.
 All metal hardware & screws to be galvanized or of otherwise approved corrosion resistance.
 Maximum 5' joist span if 2nd floor is cantilevered at ledger.
 Shear walls may not be modified unless structural calculations are submitted and approved by the Building Department
 Use of this Standard is limited to R-3 occupancies (Single Family Dwellings and Duplex)

Δ


DISCLAIMER:

Alternate deck designs may be possible when provided with an engineered analysis. Use of this conventional standard design is at the user's risk and carries no implied or inferred guarantee against failure or defects.


Western Riverside County Code Uniformity Program		
City of COACHELLA	City of Coachella	
	Building Department	
	BALCONY/DECK STANDARD	
(760)398-3002	53-990 ENTERPRISE WAY COACHELLA, CA 92236	
	Page 1 OF 4	



TEL: (760) 398-3002 WWW.COACHELLA.ORG



Ledger Detail




NOTE: This deck connection detail is based on the assumption that a minimum 1/2" thick wood member is adequately installed at all edges of the 2nd floor diaphragm. If any other material is used, such as TJI joists, a special engineered design will be required. It is the owner's responsibility to verify the presence of the appropriate rim joist.

Footing Detail



(C)



Western Riverside County Code Uniformity Program

COACHEL

City of Coachella **Building Department**


BALCONY/DECK STANDARD

53-990 ENTERPRISE WAY (760)398-3002

Page 2 OF 4



TEL: (760) 398-3002 WWW.COACHELLA.ORG





TEL: (760) 398-3002 WWW.COACHELLA.ORG

